

# Mobil Delvac Hydraulic 10W

## High Performance Hydraulic Oil

### Product Description

Mobil Delvac Hydraulic 10W is a high performance hydraulic oil formulated from advanced base oils and a balanced additive system designed to satisfy a wide range of heavy-duty hydraulic equipment requirements. This product is specifically engineered using an effective balance of ashless dispersants and metallic detergents combined with inhibitors to control oxidation, wear, corrosion and rust. Mobil Delvac Hydraulic 10W can be used in a wide range of on and off-highway hydraulic applications.

### Features and Benefits

Mobil Delvac Hydraulic 10W delivers excellent performance in a wide range of hydraulic systems and components using various multi-metal designs. The product also provides effective low and high ambient temperature performance due to high viscosity index. Its' excellent oxidation resistance delivers good performance at higher temperatures and extended operating intervals. High levels of anti-wear protection result in extended equipment life and fewer breakdowns. Mobil Delvac Hydraulic 10W is compatible with other engine oils in case of unplanned mixtures. The key benefits include:

Features	Advantages and Potential Benefits
Good protection against oil thickening, high temperature deposits, varnish, and oil degradation	Cleaner hydraulic systems Less wear especially in vanes and control valves Protects against vane sticking Extends drain intervals with oil analysis
Good anti-wear protection	Reduces premature wear and extends equipment life
Wide temperature range performance	Reduces wear at cold start-up temperatures Effective lubrication film strength at high temperatures
Protects against rust and corrosion	Longer equipment life and lower maintenance costs

### Applications

- Hydraulic systems and components used in conjunction with equipment from leading American, European, and Japanese manufacturers
- Hydraulic systems where wide ambient temperatures are encountered
- Hydraulic systems containing gears and bearings where good anti-wear properties are required
- On and off-highway industries including: trucking, construction, mining, quarrying, and agriculture

### Specifications and Approvals

**Mobil Delvac Hydraulic 10W meets the following industry specifications:**

Vickers 35VQ25



---

**Mobil Delvac Hydraulic 10W is recommended for use in the applications requiring:**

---

API CD/SF

---

## Typical Properties

<b>Mobil Delvac Hydraulic</b>	<b>10W</b>
SAE Grade	10W
Viscosity, ASTM D 445	
cSt @ 40°C	39.2
cSt @ 100°C	6.3
Viscosity Index, ASTM D 2270	109
Sulfated Ash, wt%, ASTM D 874	0.8
Total Base # , mg KOH/g, ASTM D 2896	7.3
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	226
Density @ 15°C kg/l, ASTM D 4052	0.879

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

*The Mobil logotype, the Pegasus design, and Delvac are trademarks of ExxonMobil Corporation, or one of its subsidiaries.*