



Mobiltrans SHC V30

Supreme Performance Transmission Lubricant

Product Description

Mobiltrans SHC V30 is a fully synthetic, heavy duty manual transmission lubricant engineered to meet the most demanding requirements. Recommended for year-round lubrication of manual transmissions in light to severe duty on and off highway equipment operating in a wide range of environments. Designed to provide excellent performance, Mobiltrans SHC V30 incorporates the latest lubrication technology based on synthetic basestocks and advanced additives providing significant advantages over conventional transmission oils. This advanced additive system provides outstanding high temperature detergency and dispersancy with optimised protection against thermal degradation, oxidation, wear, and corrosion. Because of its high viscosity index and synthetic base oil mixture, it provides stronger film strength at higher temperatures than conventional oils. This technology also ensures effective lubrication at extremely low temperatures without channelling. Mobiltrans SHC V30 is recommended for transmissions and non-hypoid gear-box applications.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy duty on-highway trucks in terms of load, speed, control, and reliability through innovative drive train designs. These designs have markedly changed and raised the requirements of drive train fluids to deliver higher levels of performance, while extending drain intervals. For heavy duty transmissions; friction control, wear protection, thermal stability, shear stability, rust, and corrosion protection, as well as seal protection are features that must be optimally balanced, to provide extended transmission and synchroniser life, smooth shift control, improved efficiency, and higher load capability over a wide range of applications and operating environments. The key benefits of Mobiltrans SHC V30 include:

Features	Potential Benefits
Excellent load carrying, anti-wear, and EP performance	Helps to extend transmission life and reduces cost of operation
Outstanding protection against deposit formation	Contributes to longer seal life, extended drain, and service intervals
High protection from corrosion of copper and its alloys	Helps to protect and extend the life of synchronisers
Optimised thermal and oxidation protection	Extends component life and improves efficiency
Exceptional shear stability	Aims to reduce wear during severe operation
Outstanding low temperature fluidity	Reduces wear during cold temperatures and improves shifting with quicker starts

Features	Potential Benefits
Extended drain and service interval capability	Helps to provide lower operating costs and higher productivity
Improved friction reduction properties	Potential for improved fuel economy and lowers operating costs

Applications

Recommended by ExxonMobil for use in:

- Heavy duty manual transmissions built by major European manufacturers
- On highway commercial light and heavy duty trucking, busses and vans
- Applications where severe low temperatures are encountered
- Applications where extended service intervals and warranties are required
- Use as a companion with Mobil Delvac Synthetic Gear Oils in rear axles for maximum drive train life, service efficiency, and fuel economy improvement
- NOT suitable for hypoid gear applications in differentials and final drives, either for topping-off or refills, where API service GL-5 or MIL-PRF-2105E lubricants are specified

Specifications and Approvals

Mobiltrans SHC V30 has the following builder approvals	SAE 30
Volvo 97307	X
MAN 341 Typ VR	X
MAN 341 Typ E4	X

Typical Properties

Mobiltrans SHC V30	
SAE Grade	SAE 30
Viscosity, ASTM D 445	
cSt @ 100°C	10.3
Viscosity Index, ASTM D 2270	144
Pour Point, °C, ASTM D 97	-55
Flash Point, °C, ASTM D 92	220

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobiltrans SHC V30 are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

1-2011

Esso Petroleum Company limited
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2012 Exxon Mobil Corporation. All rights reserved.