

CARTER MS 100



Lubrication



Product for open gears in sugarcane mills.

APPLICATIONS

Exposed gears

- Product based upon bitumen and very viscous oils for lubricating open gears in general and particularly those in sugarcane mills.

SPECIFICATIONS

International specifications

- NF-ISO 6743-6 category CKJ

ADVANTAGES

- Excellent extreme-pressure and anti-wear properties.
- Very good protection against corrosion and rust.
- High viscosity index.
- Excellent thermal stability.
- Excellent adherence to metal surfaces.

TYPICAL CHARACTERISTICS	METHODS	UNITS	CARTER MS 100
Density at 15 °C	ISO 3675	kg/m ³	972,5
Viscosity at 40 °C	ISO 3104	mm ² /s	6800
Open cup flash point	ISO 2592	°C	226
Timken OK load	ASTM D 2509	°C	45
4-ball EP test: welding load	DIN 53050-2	-	400

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

8 june 2001

CARTER MS 100

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

