

DACNIS P

DESCRIPTION

Highly refined mineral paraffinic base oil with specific additivation.

APPLICATIONS

- Reciprocating air compressors.
- Recommended during the running in period of some air compressors.

PROPERTIES

- Excellent resistance to oxidation.
- Good anti-rust and anti corrosive properties.
- Good compatibility with seals.

CHARACTERISTICS

CHARACTERISTICS	UNITS	DACNIS P	
		100	150
ISO Grade		100	150
Density at 15 °C	kg/m ³	885	884
Kinematic viscosity at 40 °C	mm ² /s	105	150
Kinematic viscosity at 100 °C	mm ² /s	11.6	15.1
Flash Point (COC) ASTM D 92	°C	>250	280
Pour Point	°C	- 12	- 24
Carbon Conradson Residue	%	< 0.06	0.03

Characteristics of this chart are indicative typical values

SPECIFICATIONS

- DIN 51506 VDL
 - NF-ISO 6743-3A classified DAC for severe application.
-

HANDLING, HEALTH AND SAFETY

Lubricants consisting of highly refined mineral oils with specific additives.

In normal conditions of use, these lubricants present no particular toxic hazard.

All lubricants, of any kind, should always be handled with great care, particularly avoiding any contact with the skin.

Prevent any risk of splashing, and keep away from combustible materials.

Store under cover and away from any risk of contamination.

A safety data sheet complying with current legislation is available from your Lubmarine local representative.

LUBMARINE 70/3GB - 0604



TOTAL LUBRIFIANTS
Le Diamant B - 16, rue de la République – 92922 Paris la Défense Cedex
Tel.: 33.1.41.35.59.23 – Fax: 33.1.41.35.20.92
www.lubmarine.com - catherine.signol@total.com